



Automatic Tilt Column Car Tire Changer

With premium DP30 helper arm, for rims up to 28"



▶ IT type: Bead Seater (Tubeless Inflator)

Technical Features

- ▣ Automatic tyre changer with pneumatic tilt-back tower.
- ▣ Robust Ø41mm hexagon shaft.
- ▣ Simultaneous pneumatic locking of the horizontal and vertical arms with automatic positioning of the head in the optimal work position.
- ▣ Tool head with interchangeable plastic parts for rim protection.
- ▣ Pneumatic tilting arm support column featuring high torsional rigidity in all operation positions.
- ▣ Clockwise and anticlockwise rotation of the turntable through electric motor.
- ▣ The pedal assembly can be removed allowing easy servicing.
- ▣ Protection kit for bead breaker shoe, demounting head and clamping jaw comes standard.
- ▣ Independent tire inflation bay with inflation tube, pressure gauge and pressure release button.
- ▣ Complete with lubrication filter and pressure regulator.
- ▣ **DP30 helper arm:**
 - » Rotating arm with bead pressing block for drop-center rims, to assist fitting and removal of tyres, particularly low profile tyres.
 - » Tyre lifting disk to aid in demounting difficult tyre and wheel combinations.
 - » Mid-position roller helps loosening of the second bead.



Technical Details




Stainless Tool head with interchangeable plastic parts to protect rims.



Independent tire inflation bay with inflation tube, pressure gauge and pressure release button.




Premium quality pressure regulator with water filter and lubricator.



Powerful bead breaker with 2700kg capacity.



Extractable pedal assembly for easy maintenance



Self-centering clamping jaws specially designed for motorcycle tires



Simultaneous pneumatic locking of horizontal and vertical head arms, with automatic head positioning in the ideal working condition.



Premium right helper arm with bead pressing roller, tire lifting disk and bead pressing head

Technical Specification:

Outer Clamping Size	Inner Clamping Size	Max. Wheel Dia.	Max. Wheel Width	Beadbreaking Force	Operating Pressure	Power Supply	Motor Power
15"-28"	13"-26"	1200mm	3"-15"	2700 KG	8-10 BAR	220V/50HZ/1PH 380V/50HZ/3PH	1.5KW 1.0KW

Tyre Paste Container	Paste Brush	Tool Head Protection	Bead Breaker Protection	Claw Protection	Tyre Lever

Standard Accessories