



# Hydraulic 4-Post Lift 100% Automatic Release No compressed Air Required



	4ED0300	4ED0400 ☆
Load capacity	3500 Kg	4000 Kg
Platform lengths	4370 mm	4450 mm
Platform widths	450 mm	560 mm
Width between columns	2670 mm	2670 mm
Distance between platforms	800-1235 mm	690-1015 mm
Minimum height	190 mm	150 mm
Lifting height	1700 mm	1700 mm
Lifting time	30"	30"
Overall length	5380 mm	5150 mm
Overall width	3035 mm	3035 mm
Motor	3 Phase 230/400 V 50/60 Hz. 2.2 KW	3 Phase 230/400 V 50/60 Hz. 2.2 KW

WIDER FOR 3D ALIGNMENT		
4ED0400N ☆	4ED0600 ☆	4ED1620 ☆
4000 Kg	5000 Kg	5500 Kg
4450 mm	5230 mm	5750 mm
560 mm	580 mm	600 mm
2900 mm	2900 mm	2900 mm
690-1245 mm	800-1210 mm	800-1160 mm
150 mm	150 mm	220 mm
1800 mm	1800 mm	1960 mm
45"	45"	50"
5150 mm	5950 mm	7080 mm
3265 mm	3265 mm	3265 mm
3 Phase 230/400 V 50/60 Hz. 2.2 KW	3 Phase 230/400 V 50/60 Hz. 2.2 KW	3 Phase 230/400 V 50/60 Hz. 2.2 KW

Made in Spain



Play-Detector & Turning-Plates available (EU & UK markets)



LED lighting available as an option



JACKING-BEAM available 2T & 2,6T